

P G R G D (R E C I E V E R)



Model	PGRGD
Frequency	433.92MHz
Baud rate	1200 bps
Modulation type	FSK
Channel Spacing	12.5K
Frequency stability	10ppm at -10~+60
Alert tone volume	85dBa @10cm
Current consumption Standby	3mA
Dimension	78mm 55mm 30mm
Weight	Approx. 45g
Power supply	Ni-MH 600MAH 2.4V
Battery Life	2 days (full charging)

Model	SCT-01
Frequency	433.92MHz
Baud rate	1200 bps
Modulation type	FSK
Output power	10mW
Maximum Dev.	+/- 2.5K
Channel Spacing	12.5K
Harmonic Radiation	Less -25dBm
Frequency stability	2ppm at -10~+60
Output connector	SMA(F)
Alert tone volume	80dBa @10cm
Power supply	12V/4A adapter
Operating temperature	-10~+60 deg.celcius
Operating humidity	20% RH to 80% RH (no condensation)
Dimension	Approx. 379mm 209mm 149 mm
Weight	Approx.1.9kg

S C T - 0 1 (T r a n s m i t t e r)



C H R G - 1 2 (C h a r g e r B a s e)



Model	CHRG-12
No of Slots	12 slots base
Ratio	3 by 4 rows
Full Charge	Approx. 4 hours
Dimension	309mm 115mm 45mm
Weight	Approx. 1.04kg