MITF

<u>Crowd Control</u> <u>Management System:</u>





Step 01:

Issue G3 pager to guest and (optional) enter their name and/or NRIC into the system.





Step 02:

Once the preset time is reached, the system will alert the respective guest "time-out".






Collect back the pager from guest when they

return or on their way out.

03:

Step





Easy guests and staffs notification

Improve productivity for both staff and order

Support multi outlets and sites with single transmitter

AAA Rechargeable battery with more than 96 standby hours on full charge

All activities are recorded ready for report generation

Model
Frequency
Output Power
Baud Rate
Modulation
Maximum Dev
Channel Spacing
Harmonic Radiation
Frequency Stability
Alert tone Volume
Dimension
Power Supply
Battery Life
Weight

GTX 01 433.92MHz 10mW 1200bps FSK +/- 2.5k 12.5k less -25dBm 2ppm at -10~ @+60 degree celcius 85dBa 10cm 145mm 145mm 28.5mm 5V/4A 96hours Approx. 400g







Model
Frequency
Baud Rate
Modulation
Channel Spacing
Alert tone Volume
Dimension
Power Supply
Battery Life
Weight

GP-03 433.92MHz 1200bps FSK 12.5k 85dBa 10cm 60mm 96mm 15.5mm 1.2V, Ni-HM AAA 96hours Approx. 82g